

PRODUCT DESCRIPTION

CAPO; is a water based parquet that can be used as base and top coat.

FEATURES

- High abrasion resistance
- Non yellowing
- Odorless
- High chemical resistance



Apply
with brush



Stir

RECOMMENDED USES

The product is used on parquets as base and top coat.

GLOSS OPTIONS

Product Code	Gloss
VW454.20.0000	20 ±2
VW454.50.0000	50 ±2
VW454.70.0000	70±2



Store in cool
place

PRODUCT SPECIFICATIONS

Product Type	: Water Based
Viscosity (20°C, DIN 4)	: 23 – 30"
Specific Gravity (kg/ltr)	: 1,03 – 1,05
Weight Solids (%)	: 35 - 41
Recommended Number of Coats	: 2
Recommended Application (gr/m²)	: 60 - 100
Practical Coverage (m²/ltr)	: 10 - 18

Dry Time (20°C, % 45-65 RH, 100 g/m²)

Dust free	: 1 h
Touch dry	: 1,5 h
Sanding	: 16 h
Waiting between coats	: 4 h



Protect from
freezing

SURFACE PREPARATION

Surface must be clean and dust free; remove all dirt (dust, wax etc.) Waterborne products are tend to raise the fiber of the woods. To minimize fiber rising substrate has to be sanded with 150-180 grit paper. The humidity level of the wood must be 12-14 %.

APPLICATION

Mix well before use. 4 hours after first coat surface is sanded with 220 grit paper. If the time interval between second and third coat is less than 4 hour, there is no need to sand. In order to stain the wood use water insoluble stains. At low temperatures and/or high relative humidity drying time get longer. Thus, drying must be carried out in areas with good air ventilation

Application Equipment

- Roll
- Brush

STORAGE & HANDLING

If properly stored at temperatures between 5 and 35 °C, shelf life is 12 months.

Store in a cool, dry place and away from heat.

Close all containers after use.

HEALTH & SAFETY

For full Health and Safety information please refer to Material Safety Data Sheet.

Gloves and suitable protective equipment must be worn while using these products.

Good ventilation must be provided in the working environment.

WARNING

During application the temperature of the product, the coating, the application area and the substrate should never fall 15°C. Otherwise, the performance of the coating will decrease.

Before usage, check homogeneity and stir well.

Application tools must be cleaned with water and the coating left overs (washing waters, water of spray booths and used coatings) must be disposed of according to local regulations. Never dispose residues directly into drains.

TRANSPORT INFORMATION

Freight Classification	: Varnish
Packaging	: 5 LT