

PRODUCT DESCRIPTION

HPA 100; is additive for improving performance of water based products. The part of the sunscreen, solutions and oils that are not absorbed by the skin used in the summer can deform the water-based coating surface when it comes in contact with the furniture. It is recommended to use HPA 100 to prevent and / or reduce the deformation that occurs. It can be used in air-drying environments. Reactive in room conditions.

FEATURES

- Improving high resistance to sunoil

RECOMMENDED USES

It can be used in water-based products. The usage rate and effect change depending on the product type.

PRODUCT SPECIFICATIONS

Product Type	: Water Based
Viscosity (@ 25°C /DIN4)	: 10±2"
Specific Gravity (kg/l)	: 1,060 ± 0,02
pH (25°C)	: ± 10,5

APPLICATION

The sun oil protector is packaged ready for use. Application is made by mixing directly with the product. Recommended maximum usage rate is 1-3% by weight. The usage rate varies depending on the product and needs. It is recommended to use the prepared mixture within the same day.

STORAGE & HANDLING

The shelf life is 12 months if the products a restored in an environment with temperature between 5 - 35°C.

Coating left overs (washing waters, waters from spray booths, used coatings) must be disposed according to local regulations. Never dispose residues directly into drains.

Application tools must be cleaned with water after use.

Keep in dry and cool storage area.

HEALTH & SAFETY

Observe the precautionary notices which are displayed on the container.

Good ventilation must be provided in the working environment.

For full Health and Safety information, please refer to Safety Data Sheet.

Gloves and suitable protective equipment must be worn while using these products.

WARNING

The product application on substrate must be done in an environment with no less than 12°C.

Coatings applications at low temperatures may cause lower chemical and mechanical properties than standard performances.

Mix the product before use.

Application equipment should be cleaned with water and product residues should never be given to the sewer.

TRANSPORT INFORMATION

Freight Classification	: Additive
Packaging	: 0,05 L



Stir



Store in cool
place



Protect from
freezing