

PRODUCT DESCRIPTION

LATYGRUND is semi-transparency water based base coat. It is colorable product.

FEATURES

- Resist and protect against UV Lights
- Chemical structure with impregnation properties
- The feeling of depth in wood texture
- High resistance to moisture
- It doesn't contain pesticide and mercury. Contain IPBC

RECOMMENDED USES

It is used for facades of wooden houses, wooden panels, wooden doors, arbor, pergola and windows.

PRODUCT SPECIFICATIONS

Product Type	: Water Based
Viscosity (@ 25°C /DIN4)	: 13"
Specific Gravity (kg/lit)	: 1,02 ± 0,02
Weight Solids (%)	: 10 ± 1
pH	: 7,5
Recommended Number of Coats	: 2
Recommended Application (gr/m²)	: 50 - 80
Practical Coverage (m²/lt)	: 10 - 12
Forced Air Drying (150 g/m² application)	
Flash off	: 15 min. (30°C)
Oven/Laminar air	: 30 min. (30°C)
Cooling	: 15 min. (20°C)
Dry Time (20°C, % 45-65 RH, 100 g/m²)	
Dust free	: 10 min.
Touch dry	: 30 min.
Sanding	: 2 hours
Waiting between coats	: 4 - 6 hours
Stackable	: 12 hours

COLOR OPTIONS

Color Code	Color
0000	CLEAR
1550	VERDE
1551	TEAK
1553	PINO
1554	CASTAGNO
1555	DARK NOCE
1556	NOCE
1557	MAHAGONY
1558	CHERRY
1559	OAK
1570	GREY

SURFACE PREPARATION

The substrate has to be properly sanded and cleaned up from dust particles.

Wood must be well seasoned (max. 12% humidity). Always clean well the surfaces, removing all traces of grease, waxes and resins. Perform sanding with 180 grit paper for hardwoods.

APPLICATION

Conventional Spray: Recommended to use 2-2,5 mm nozzle with 3-4 air bar.

Flow-coating system: Use diaphragm pump.

Brush type: Use only synthetic hair.

Application Equipment

- Spray
- Brush

STORAGE & HANDLING

The shelf life is 12 months if the products are stored in an environment with temperature between 5 - 35°C.

Coating left overs (washing waters, waters from spray booths, used coatings) must be disposed according to local regulations. Never dispose residues directly into drains.

Application tools must be cleaned with water after use.

Keep in dry and cool storage area

HEALTH & SAFETY

Observe the precautionary notices which are displayed on the container.

Good ventilation must be provided in the working environment.

For full Health and Safety information, please refer to Safety Data Sheet.

Gloves and suitable protective equipment must be worn while using these products.

WARNING

The product application on substrate must be done in an environment with no less than 12°C.

Coatings applications at low temperatures may cause lower chemical and mechanical properties than standard performances.

Mix the product before use.

Application equipment should be cleaned with water and product residues should never be given to the sewer.

TRANSPORT INFORMATION

Freight Classification : Base Coat

Packaging : 0,75 LT, 2,5 LT, 20 LT



Apply with
brush



Apply with
spray



Stir



Store in cool
place



Protect from
freezing